

NUMBER AND QUANTITY	W-11 1 (ONE)
DESCRIPTION OF DOOR PANEL, FRAME AND FINISH	Custom aluminium - according to spec approval with a continuous clear silicone seal around all construction openings.(Colour according to the architect).
IRONMONGERY	As supplied by specialist.
SECURITY	As supplied by specialist.
GLASS AND GLAZING	Safety glass as supplied by the manufacturer to comply with AAAMSA and SANS 10400.

NUMBER AND QUANTITY	W-12 6 (SIX)
DESCRIPTION OF DOOR PANEL, FRAME AND FINISH	Custom aluminium windowframe powdercoated with INTERPON finish according to specialist subcontractor specification as well as architects approval with a continuous clear silicone seal around all construction openings.(Colour according to the architect).
IRONMONGERY	As supplied by specialist
SECURITY	Custom fitted TRELLIDOR CLEARGUARD SECURITY SCREENS - custom sized stainless steel see-through wire mesh in a full architectural grade aluminium frame (standard profile: 45mm) with customised stainless steel hinges for added protection to match window frame (colour: acc. to architect) with fixed frame fitted to the window reveal with a powder coat finish or similar approved security products.
GLASS AND GLAZING	Top panel - Safety glass as supplied by the manufacturer to comply with AAAMSA and SANS 10400. Bottom panel - 6.38mm white translucent safety glass to comply with AAMSA & SANS 10400.

NUMBER AND QUANTITY	W-13 3 (THREE)
DESCRIPTION OF DOOR PANEL, FRAME AND FINISH	Custom aluminium windowframe powdercoated with INTERPON finish according to specialist subcontractor specification as well as architects approval with a continuous clear silicone seal around all construction openings.(Colour according to the architect).
IRONMONGERY	As supplied by specialist
SECURITY	Custom fitted TRELLIDOR CLEARGUARD SECURITY SCREENS - custom sized stainless steel see-through wire mesh in a full architectural grade aluminium frame (standard profile: 45mm) with customised stainless steel hinges for added protection to match window frame (colour: acc. to architect) with fixed frame fitted to the window reveal with a powder coat finish or similar approved security products.
GLASS AND GLAZING	Top panel - Safety glass as supplied by the manufacturer to comply with AAAMSA and SANS 10400. Bottom panel - 6.38mm white translucent safety glass to comply with AAMSA & SANS 10400.

NUMBER AND QUANTITY	W-14 1 (ONE)
DESCRIPTION OF DOOR PANEL, FRAME AND FINISH	Custom aluminium windowframe powdercoated with INTERPON finish according to specialist subcontractor specification as well as architects approval with a continuous clear silicone seal around all construction openings.(Colour according to the architect).
IRONMONGERY	As supplied by specialist
SECURITY	Custom fitted TRELLIDOR CLEARGUARD SECURITY SCREENS - custom sized stainless steel see-through wire mesh in a full architectural grade aluminium frame (standard profile: 45mm) with customised stainless steel hinges for added protection to match window frame (colour: acc. to architect) with fixed frame fitted to the window reveal with a powder coat finish or similar approved security products.
GLASS AND GLAZING	Safety glass as supplied by the manufacturer to comply with AAAMSA and SANS 10400.

NUMBER AND QUANTITY	W-15 1 (ONE)
DESCRIPTION OF DOOR PANEL, FRAME AND FINISH	Custom aluminium double door; all powdercoated with INTERPON finish according to specialist subcontractor specifications as well as architects approval with a continuous clear silicone seal around all construction openings.(Colour according to the architect).
IRONMONGERY	As supplied by specialist
SECURITY	Custom fitted TRELLIDOR CLEARGUARD SECURITY SCREENS - custom sized stainless steel see-through wire mesh in a full architectural grade aluminium frame (standard profile: 45mm) with customised stainless steel hinges for added protection to match window frame (colour: acc. to architect) with fixed frame fitted to the window reveal with a powder coat finish or similar approved security products.
GLASS AND GLAZING	Safety glass as supplied by the manufacturer to comply with AAAMSA and SANS 10400.

NUMBER AND QUANTITY	W-16 1 (ONE)
DESCRIPTION OF DOOR PANEL, FRAME AND FINISH	Custom aluminium windowframe powdercoated with INTERPON finish according to specialist subcontractor specifications as well as architects approval with a continuous clear silicone seal around all construction openings.(Colour according to the architect).
IRONMONGERY	As supplied by specialist
SECURITY	Custom fitted TRELLIDOR CLEARGUARD SECURITY SCREENS - custom sized stainless steel see-through wire mesh in a full architectural grade aluminium frame (standard profile: 45mm) with customised stainless steel hinges for added protection to match window frame (colour: acc. to architect) with fixed frame fitted to the window reveal with a powder coat finish or similar approved security products.
GLASS AND GLAZING	Safety glass as supplied by the manufacturer to comply with AAAMSA and SANS 10400.

NUMBER AND QUANTITY	W-17 1 (ONE)
DESCRIPTION OF DOOR PANEL, FRAME AND FINISH	Custom aluminium windowframe powdercoated with INTERPON finish according to specialist subcontractor specification as well as architects approval with a continuous clear silicone seal around all construction openings.(Colour according to the architect).
IRONMONGERY	As supplied by specialist
SECURITY	Custom fitted TRELLIDOR CLEARGUARD SECURITY SCREENS - custom sized stainless steel see-through wire mesh in a full architectural grade aluminium frame (standard profile: 45mm) with customised stainless steel hinges for added protection to match window frame (colour: acc. to architect) with fixed frame fitted to the window reveal with a powder coat finish or similar approved security products.
GLASS AND GLAZING	6.38mm white translucent safety glass to comply with AAMSA & SANS 10400.

NUMBER AND QUANTITY	W-18 2 (TWO)
DESCRIPTION OF DOOR PANEL, FRAME AND FINISH	Custom aluminium windowframe powdercoated with INTERPON finish according to specialist subcontractor specification as well as architects approval with a continuous clear silicone seal around all construction openings.(Colour according to the architect).
IRONMONGERY	As supplied by specialist
SECURITY	Custom fitted TRELLIDOR CLEARGUARD SECURITY SCREENS - custom sized stainless steel see-through wire mesh in a full architectural grade aluminium frame (standard profile: 45mm) with customised stainless steel hinges for added protection to match window frame (colour: acc. to architect) with fixed frame fitted to the window reveal with a powder coat finish or similar approved security products.
GLASS AND GLAZING	6.38mm white translucent safety glass to comply with AAMSA & SANS 10400.

NUMBER AND QUANTITY	W-19 1 (ONE)
DESCRIPTION OF DOOR PANEL, FRAME AND FINISH	Custom aluminium door- & (x3) sidelight & (x1) top hung; all powdercoated with INTERPON finish according to specialist subcontractor specifications as well as architects approval with a continuous clear silicone seal around all construction openings.(Colour according to the architect).
IRONMONGERY	As supplied by specialist
SECURITY	Custom fitted TRELLIDOR CLEARGUARD SECURITY SCREENS - custom sized stainless steel see-through wire mesh in a full architectural grade aluminium frame (standard profile: 45mm) with customised stainless steel hinges for added protection to match window frame (colour: acc. to architect) with fixed frame fitted to the window reveal with a powder coat finish or similar approved security products.
GLASS AND GLAZING	6.38mm white translucent safety glass to comply with AAMSA & SANS 10400.

NUMBER AND QUANTITY	W-20 1 (ONE)
DESCRIPTION OF DOOR PANEL, FRAME AND FINISH	Custom aluminium windowframe powdercoated with INTERPON finish according to specialist subcontractor specification as well as architects approval with a continuous clear silicone seal around all construction openings.(Colour according to the architect).
IRONMONGERY	As supplied by specialist
SECURITY	Custom fitted TRELLIDOR CLEARGUARD SECURITY SCREENS - custom sized stainless steel see-through wire mesh in a full architectural grade aluminium frame (standard profile: 45mm) with customised stainless steel hinges for added protection to match window frame (colour: acc. to architect) with fixed frame fitted to the window reveal with a powder coat finish or similar approved security products.
GLASS AND GLAZING	Safety glass as supplied by the manufacturer to comply with AAAMSA and SANS 10400.

NUMBER AND QUANTITY	W-21 1 (ONE)
DESCRIPTION OF DOOR PANEL, FRAME AND FINISH	Custom aluminium shopfront with INTERPON powdercoated finish by specialist subcontractor to architects approval with a continuous clear silicone seal around all construction openings.(Colour according to the architect).
IRONMONGERY	As supplied by specialist
SECURITY	Custom fitted TRELLIDOR CLEARGUARD SECURITY SCREENS - custom sized stainless steel see-through wire mesh in a full architectural grade aluminium frame (standard profile: 45mm) with customised stainless steel hinges for added protection to match window frame (colour: acc. to architect) with fixed frame fitted to the window reveal with a powder coat finish or similar approved security products.
GLASS AND GLAZING	6.38mm white translucent safety glass to comply with AAMSA & SANS 10400.

NUMBER AND QUANTITY	W-22 1 (ONE)
DESCRIPTION OF DOOR PANEL, FRAME AND FINISH	Custom aluminium door- & (x1) sidelights & (x1) top hung; all powdercoated with INTERPON finish according to specialist subcontractor specifications as well as architects approval with a continuous clear silicone seal around all construction openings.(Colour according to the architect).
IRONMONGERY	As supplied by specialist
SECURITY	Custom fitted TRELLIDOR CLEARGUARD SECURITY SCREENS - custom sized stainless steel see-through wire mesh in a full architectural grade aluminium frame (standard profile: 45mm) with customised stainless steel hinges for added protection to match window frame (colour: acc. to architect) with fixed frame fitted to the window reveal with a powder coat finish or similar approved security products.
GLASS AND GLAZING	Safety glass as supplied by the manufacturer to comply with AAAMSA and SANS 10400.

NUMBER AND QUANTITY	W-23 1 (ONE)
DESCRIPTION OF DOOR PANEL, FRAME AND FINISH	Custom aluminium door- & (x3) sidelight & (x1) top hung; all powdercoated with INTERPON finish according to specialist subcontractor specifications as well as architects approval with a continuous clear silicone seal around all construction openings.(Colour according to the architect).
IRONMONGERY	As supplied by specialist
SECURITY	Custom fitted TRELLIDOR CLEARGUARD SECURITY SCREENS - custom sized stainless steel see-through wire mesh in a full architectural grade aluminium frame (standard profile: 45mm) with customised stainless steel hinges for added protection to match window frame (colour: acc. to architect) with fixed frame fitted to the window reveal with a powder coat finish or similar approved security products.
GLASS AND GLAZING	Safety glass as supplied by the manufacturer to comply with AAAMSA and SANS 10400.

NUMBER AND QUANTITY	W-24 1 (ONE)
DESCRIPTION OF DOOR PANEL, FRAME AND FINISH	Custom aluminium windowframe powdercoated with INTERPON finish according to specialist subcontractor specification as well as architects approval with a continuous clear silicone seal around all construction openings.(Colour according to the architect).
IRONMONGERY	As supplied by specialist
SECURITY	Custom fitted TRELLIDOR CLEARGUARD SECURITY SCREENS - custom sized stainless steel see-through wire mesh in a full architectural grade aluminium frame (standard profile: 45mm) with customised stainless steel hinges for added protection to match window frame (colour: acc. to architect) with fixed frame fitted to the window reveal with a powder coat finish or similar approved security products.
GLASS AND GLAZING	Safety glass as supplied by the manufacturer to comply with AAAMSA and SANS 10400.

NUMBER AND QUANTITY	W-25 2 (TWO)
DESCRIPTION OF DOOR PANEL, FRAME AND FINISH	Custom aluminium windowframe powdercoated with INTERPON finish according to specialist subcontractor specification as well as architects approval with a continuous clear silicone seal around all construction openings.(Colour according to the architect).
IRONMONGERY	As supplied by specialist
SECURITY	Custom fitted TRELLIDOR CLEARGUARD SECURITY SCREENS - custom sized stainless steel see-through wire mesh in a full architectural grade aluminium frame (standard profile: 45mm) with customised stainless steel hinges for added protection to match window frame (colour: acc. to architect) with fixed frame fitted to the window reveal with a powder coat finish or similar approved security products.
GLASS AND GLAZING	Safety glass as supplied by the manufacturer to comply with AAAMSA and SANS 10400.

NOTES
UNDER NO CIRCUMSTANCES MAY THIS DOCUMENT BE REPRODUCED WITHOUT THE CONSENT OF DE JONG DESIGN STUDIO CC.
DRAWINGS MAY NOT BE SCALED.
ALL DIMENSIONS AND HEIGHTS MUST BE CORRELATED BEFORE ANY WORK COMMENCES OR BEFORE MATERIALS ARE ORDERED.
IT IS THE CONTRACTOR'S RESPONSIBILITY TO SET-OUT CONSTRUCTION WORK ACCURATELY ON SITE WITH REFERENCE TO SITE BOUNDARIES, BUILDING LINES SERVITUDES AND ESPECIALLY IN CIRCUMSTANCES WHERE WORK CONNECT WITH EXISTING STRUCTURES.
ALL FLOOR LEVEL HEIGHTS INDICATED ON DRAWINGS REFER TO UNFINISHED LEVELS AND ANY AMBIGUOUS OR CONTRADICTORY INFORMATION SHOULD IMMEDIATELY BE CO-ORDINATED WITH THE ARCHITECT. A FULL SET OF DRAWINGS SHOULD BE KEPT ON SITE BY THE CONTRACTOR.
ALL DIMENSIONS INDICATE ON DRAWINGS SHOULD BE SET-OUT ON A LEVEL HORIZONTAL PLANE.
THE CONTRACTOR SHOULD MAKE USE OF CORNER PROFILES MARKED ON 85MM BRICK GAUGE, UNLESS DIFFERENTLY SPECIFIED.
THE CONTRACTOR IS RESPONSIBLE TO USE APPROVED DAMP PROOF COURSE IN EXTERNAL WALLS AND DAMP PROOF MEMBRANES UNDER FLOOR SLABS.
THE QUALITY OF ALL MATERIALS AND WORKMANSHIP SHOULD COMPLY WITH THE RELEVANT S.A.B.S. SPECIFICATIONS AND STANDARDS.
ALL MINIMUM STANDARDS AS SET OUT IN THE NATIONAL BUILDING REGULATIONS AND STANDARDS ACT SANS 10400 ARE ALSO APPLICABLE IN SITUATIONS WHERE NOT SPECIFICALLY REFERRED TO.
ALL GEYSERS AND WARM WATER MUST COMPLY WITH SANS 10254. WATER RETICULATION INSTALLATION MUST COMPLY WITH SANS 10252-1 ALL UPVC PIPES MUST COMPLY WITH SANS 966 ALL COPPER PIPES MUST COMPLY WITH SANS 460 ALL HDPE PIPES MUST COMPLY WITH SANS 533 ALL TAPS AND MIXERS MUST COMPLY WITH SANS 226. SANS 1026, SANS 1808-35 EN 1808-37.

No	REVISION	DATE	APPROVED

CONSULTANT

deStudio Architects & Urban Planners
Reg no.: CK 2009/1157/123
2 Second Street, Po Box 26079,
Dan Pienaar, Bloemfontein
9310
Tel: +27 (0) 51 436 0130
Fax: +27 (0) 51 436 1177
Addie de Jong
Pr. Arch 21159, Pr. Pln A/14230/11
+27 (0) 84 400 9364
Alphonse de Jong
Pr. Arch 7832
+27 (0) 82 946 0777
info@deStudio.co.za
www.deStudio.co.za

Architects & Urban Planners

PROFESSIONAL ARCHITECT
ADELE DE JONG
12-21 PM (Johnschoorweg) on 01 Jun 2021

PROGRAMME MANAGER

iot
Independent Development Trust

CLIENT

Province of the NORTHERN CAPE
Department of Health

LOGOBATE PHC PROJECT

UPGRADE AND REFURBISHMENT TO EXISTING HEALTH FACILITY, ON PORTION 60 ON THE FARM 219 KURUMAN DISTRICT NORTHERN CAPE

DRAWN	DATE
A.d.J./A.C.d.J.	21/9/2026
APPROVED	DATE
SCALE	ISSUED
AS INDICATED	21/9/2026
DRAWING STATUS	00 DRAWING No
TENDER DRAWINGS	14-158_P4_14